

# PRODUCT OVERVIEW

01-2024

UTAX // COLOR AND MONO MULTIFUNCTIONAL SYSTEMS



# Content

## Color Systems

A3 Multifunctional Systems page 3

A4 Multifunctional Systems page 5

A4 Print Systems page 8

## Mono Systems

A3 Multifunctional Systems page 9

A4 Multifunctional Systems page 11

A3 Print Systems page 15

A4 Print Systems page 16

# A3 Multifunctional Systems



Optional features are marked in grey font.



		P-C2480i MFP	2508ci	3508ci	4008ci
<b>COPY</b>	COPY SPEED	24 A4 pages/min, max 12 A3 pages/min in colour and in b/w	25 A4 / 12 A3 pages/min in colour and b/w	35 A4 / 17 A3 pages/min in colour and b/w	40 A4 / 20 A3 pages/min in colour and b/w
	COPY RESOLUTION	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	GREYSCALES	256	256	256	256
	STANDARD PAPER FEED	600 (500 + 100 sheets)	1,150 (2 x 500 + 150 sheets)	1,150 (2 x 500 + 150 sheets)	1,150 (2 x 500 + 150 sheets)
	OPTIONAL PAPER FEED	1 or 2 x 500 sheets	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible
	PAPER CAPACITY, MAX	1,600 sheets	7,150 sheets	7,150 sheets	7,150 sheets
	PAPER FORMAT	A6R-A3	A6R-SRA3/A3+	A6R-SRA3/A3+	A6R-SRA3/A3+
	ORIGINAL FEEDER	Standard	Option: DP-7140, DP-7150, DP-7160 or DP-7170	Option: DP-7140, DP-7150, DP-7160 or DP-7170	Option: DP-7140, DP-7150, DP-7160 or DP-7170
	DUPLEX	Standard	Standard	Standard	Standard
	SYSTEM MEMORY	1.5 GB (max 3 GB)	4 GB RAM, 32 GB SSD/320 GB HDD or 1 TB HDD	4 GB RAM, 32 GB SSD/320 GB HDD or 1 TB HDD	4 GB RAM, 64 GB SSD/320 GB HDD or 1 TB HDD
ZOOM	25%-400%	25%-400%	25%-400%	25%-400%	
CABINET	Option: no. 62	Option: no. 81	Option: no. 81	Option: no. 81	
<b>PRINT</b>	TYPE	Integrated within the system	Integrated within the system	Integrated within the system	Integrated within the system
	INTERFACES	USB 2.0, 10/100/1000BaseTX, USB host (2), NFC, Wi-Fi	USB 3.0, USB 2.0, 10/100/1000BaseTX, USB host, NFC	USB 3.0, USB 2.0, 10/100/1000BaseTX, USB host, NFC	USB 3.0, USB 2.0, 10/100/1000BaseTX, USB host, NFC
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.9	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.9	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.9	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.9
EMULATIONS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIC, PDF 1.7	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIC, PDF 2.0, XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIC, PDF 2.0, XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIC, PDF 2.0, XPS	
<b>NETWORK</b>	INTERFACES	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	NETWORK PROTOCOLS	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	OPERATING SYSTEMS	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022
<b>SCAN</b>	SCAN TYPE	CIS colour and b/w	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w
	SCAN RESOLUTION	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	INTERFACES	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	NETWORK PROTOCOLS	TCP/IP	TCP/IP	TCP/IP	TCP/IP
<b>FAX</b>	ORIGINALS	max A3	max A3	max A3	max A3
	MODEM SPEED	33.6 kbps	33.6 kbps	33.6 kbps	33.6 kbps
	COMPRESSION METHOD	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	ONE-TOUCH DIAL/ABBR. DIAL	100/200	1,000/2,000	1,000/2,000	1,000/2,000

# A3 Multifunctional Systems



Optional features are marked in grey font.

		5008ci	6008ci	7008ci	8307ci
<b>COPY</b>	COPY SPEED	50 A4 / 25 A3 pages/min in colour and b/w	60 A4 / 30 A3 pages/min in colour and b/w	70 A4 / 35 A3 pages/min in colour and b/w	70/83 A4 / 35/41 A3 pages/min in colour and b/w
	COPY RESOLUTION	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	GREYSCALES	256	256	256	256
	STANDARD PAPER FEED	1,150 (2 x 500 + 150 sheets)	1,150 (2 x 500 + 150 sheets)	1,150 (2 x 500 + 150 sheets)	4,150 (2 x 500 + 2 x 1,500 + 150 sheets)
	OPTIONAL PAPER FEED	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible
	PAPER CAPACITY, MAX	7,150 sheets	7,650 sheets	7,650 sheets	7,650 sheets
	PAPER FORMAT	A6R-SRA3/A3+	A6R-SRA3/A3+	A6R-SRA3/A3+	A6R-A3+
	ORIGINAL FEEDER	Option: DP-7150, DP-7160 or DP-7170	Option: DP-7150, DP-7160 or DP-7170	Option: DP-7150, DP-7160 or DP-7170	Standard (dual scan with multi-feed detection)
	DUPLEX	Standard	Standard	Standard	Standard
	SYSTEM MEMORY	4 GB RAM, 64 GB SSD/320 GB HDD or 1 TB HDD	4 GB RAM, 64 GB SSD/320 GB HDD or 1 TB HDD	4 GB RAM, 64 GB SSD/320 GB HDD or 1 TB HDD	4.5 GB RAM, 8 GB SSD/320 GB HDD
ZOOM	25%-400%	25%-400%	25%-400%	25%-400%	
CABINET	Option: no. 81	Option: no. 81	Option: no. 81	--	
<b>PRINT</b>	TYPE	Integrated within the system	Integrated within the system	Integrated within the system	Integrated within the system
	INTERFACES	USB 3.0, USB 2.0, 10/100/1000BaseTX, USB host, NFC	USB 3.0, USB 2.0, 10/100/1000BaseTX, USB host, NFC	USB 3.0, USB 2.0, 10/100/1000BaseTX, USB host, NFC	USB 2.0, 10/100/1000BaseTX, USB host, NFC
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.9	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.9	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.9	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.9
	EMULATIONS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIC, PDF 2.0, XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIC, PDF 2.0, XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIC, PDF 2.0, XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIC
<b>NETWORK</b>	INTERFACES	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	NETWORK PROTOCOLS	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	OPERATING SYSTEMS	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022
<b>SCAN</b>	SCAN TYPE	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w
	SCAN RESOLUTION	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	INTERFACES	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	NETWORK PROTOCOLS	TCP/IP	TCP/IP	TCP/IP	TCP/IP
<b>FAX</b>	ORIGINALS	max A3	max A3	max A3	max A3
	MODEM SPEED	33.6 kbps	33.6 kbps	33.6 kbps	33.6 kbps
	COMPRESSION METHOD	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	ONE-TOUCH DIAL/ABBR. DIAL	1,000/2,000	1,000/2,000	1,000/2,000	1,000/2,000

# A4 Multifunctional Systems

Optional features are marked in grey font.



		302ci	352ci	402ci	502ci
<b>COPY</b>	COPY SPEED	30 A4 pages/min in colour and b/w	35 A4 pages/min in colour and b/w	40 A4 pages/min in colour and b/w	50 A4 pages/min in colour and b/w
	COPY RESOLUTION	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	GREYSCALES	256	256	256	256
	STANDARD PAPER FEED	600 (1 x 500 + 100 sheets)	600 (1 x 500 + 100 sheets)	600 (1 x 500 + 100 sheets)	600 (1 x 500 + 100 sheets)
	OPTIONAL PAPER FEED	1 x 500 + 2 x 500 or 1 x 2,000 sheets	1 x 500 + 2 x 500 or 1 x 2,000 sheets	1 x 500 + 2 x 500 or 1 x 2,000 sheets	1 x 500 + 2 x 500 or 1 x 2,000 sheets
	PAPER CAPACITY, MAX	3,100 sheets	3,100 sheets	3,100 sheets	3,100 sheets
	PAPER FORMAT	A6R-A4	A6R-A4	A6R-A4	A6R-A4
	ORIGINAL FEEDER	Standard	Option: DP-5100, DP-5120, DP-5130	Option: DP-5100, DP-5120, DP-5130	Option: DP-5100, DP-5120, DP-5130
	DUPLEX	Standard	Standard	Standard	Standard
	SYSTEM MEMORY	1,536 MB RAM, (max 3,072 MB RAM)	4 GB RAM, 16 GB SSD/320 GB HDD	4 GB RAM, 8 GB SSD, 320 GB HDD	4 GB RAM, 8 GB SSD, 320 GB HDD
ZOOM	25%-400%	25%-400%	25%-400%	25%-400%	
CABINET	Option: high no. 74, low no. 75	Option: high no. 74, low no. 75	Option: high no. 74, low no. 75	Option: high no. 74, low no. 75	
<b>PRINT</b>	TYPE	Integrated within the system	Integrated within the system	Integrated within the system	Integrated within the system
	INTERFACES	USB 2.0 (opt.), 10/100/1000BaseTX, USB host (2)	USB 2.0 (opt.), 10/100/1000BaseTX, USB host (3), NFC	USB 2.0 (opt.), 10/100/1000BaseTX, USB host (3), NFC	USB 2.0 (opt.), 10/100/1000BaseTX, USB host (3), NFC
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.9	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.9	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.9	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.9
	EMULATIONS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE Ilc, PDF 1.7, XPS, OpenXPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE Ilc, PDF 1.7, XPS, OpenXPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE Ilc, PDF 1.7, XPS, OpenXPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE Ilc, PDF 1.7, XPS, OpenXPS
<b>NETWORK</b>	INTERFACES	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	NETWORK PROTOCOLS	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	OPERATING SYSTEMS	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022
<b>SCAN</b>	SCAN TYPE	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w
	SCAN RESOLUTION	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	INTERFACES	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0
	NETWORK PROTOCOLS	TCP/IP	TCP/IP	TCP/IP	TCP/IP
<b>FAX</b>	ORIGINALS	max A4	max A4	max A4	max A4
	MODEM SPEED	33,6 kbps	33,6 kbps	33,6 kbps	33,6 kbps
	COMPRESSION METHOD	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	ONE-TOUCH DIAL/ABBR. DIAL	100/200	1,000/2,000	1,000/2,000	1,000/2,000

# A4 Multifunctional Systems



		P-C2655w MFP	358ci	458ci
<b>COPY</b>	COPY SPEED	26 A4 pages/min in colour and b/w	35 A4 pages/min in colour and b/w	45 A4 pages/min in colour and b/w
	COPY RESOLUTION	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	GREYSCALES	256	256	256
	STANDARD PAPER FEED	300 (1 x 250 + 50 sheets)	350 (1 x 250 + 100 sheets)	650 (1 x 550 + 100 sheets)
	OPTIONAL PAPER FEED	1 x 250 sheets	3 x 550 sheets	4 x 550 sheets
	PAPER CAPACITY, MAX	550 sheets	2,000 sheets	2,850 sheets
	PAPER FORMAT	A6R-A4	A6R-A4	A6R-A4
	ORIGINAL FEEDER	Standard (Duplex-Scan)	Standard (dual scan)	Standard (dual scan with multi-feed detection)
	DUPLEX	Standard	Standard	Standard
	SYSTEM MEMORY	512 MB (max 1,536 MB)	2 GB RAM (max 3 GB RAM)/64/256/512 GB SSD	2 GB RAM (max 3 GB RAM)/64/256/512 GB SSD
ZOOM	25%–400%	25%–400%	25%–400%	
CABINET	Option: no. 77	Option: high no. 82, low no. 83	Option: high no. 82, low no. 83	
<b>PRINT</b>	TYPE	Integrated within the system	Integrated within the system	Integrated within the system
	INTERFACES	USB 2.0, 10/100/1000BaseTX, USB host, SD slot, Wi-Fi	USB 2.0, 10/100/1000 BaseTX, USB host (2)	USB 2.0, 10/100/1000 BaseTX, USB host (2)
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Mac ex OS 10.9	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.14
	EMULATIONS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS, Open XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS
<b>NETWORK</b>	INTERFACES	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	NETWORK PROTOCOLS	TCP/IP, Net BEUI	TC P/IP, Net BEUI	TC P/IP, Net BEUI
	OPERATING SYSTEMS	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022
<b>SCAN</b>	SCAN TYPE	CIS colour and b/w	CCD colour and b/w	CCD colour and b/w
	SCAN RESOLUTION	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	INTERFACES	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0
	NETWORK PROTOCOLS	TCP/IP	TCP/IP	TCP/IP
<b>FAX</b>	ORIGINALS	max A4	max A4	max A4
	MODEM SPEED	33.6 kbps	33.6 kbps	33.6 kbps
	COMPRESSION METHOD	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	ONE-TOUCH DIAL/ABBR. DIAL	100/100	100/200	100/200

Optional features are marked in grey font.

# A4 Multifunctional Systems

Optional features are marked in grey font.



		P-C3563i MFP	P-C3567i MFP	P-C4063i MFP	P-C4067i MFP
<b>COPY</b>	COPY SPEED	35 A4 pages/min in colour and b/w	35 A4 pages/min in colour and b/w	40 A4 pages/min in colour and b/w	40 A4 pages/min in colour and b/w
	COPY RESOLUTION	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	GREYSCALES	256	256	256	256
	STANDARD PAPER FEED	350 (1 x 250 + 100 sheets)	350 (1 x 250 + 100 sheets)	350 (1 x 250 + 100 sheets)	350 (1 x 250 + 100 sheets)
	OPTIONAL PAPER FEED	3 x 550 sheets	3 x 550 sheets	3 x 550 sheets	3 x 550 sheets
	PAPER CAPACITY, MAX	2,000 sheets	2,000 sheets	2,000 sheets	2,000 sheets
	PAPER FORMAT	A6R-A4	A6R-A4	A6R-A4	A6R-A4
	ORIGINAL FEEDER	Standard (dual scan)	Standard (dual scan)	Standard (dual scan with multi-feed detection)	Standard (dual scan with multi-feed detection)
	DUPLEX	Standard	Standard	Standard	Standard
	SYSTEM MEMORY	1.5 GB RAM (max 3 GB RAM)/64/256/512 GB SSD RAM	1.5 GB RAM (max 3 GB RAM)/64/256/512 GB SSD RAM	2 GB RAM (max 3 GB RAM)/64/256/512 GB SSD RAM	2 GB RAM (max 3 GB RAM)/64/256/512 GB SSD RAM
ZOOM	25%–400%	25%–400%	25%–400%	25%–400%	
CABINET	Option: high no. 82, low no. 83	Option: high no. 82, low no. 83	Option: high no. 82, low no. 83	Option: high no. 82, low no. 83	
<b>PRINT</b>	TYPE	Integrated within the system	Integrated within the system	Integrated within the system	Integrated within the system
	INTERFACES	USB 2.0, 10/100/1000BaseTX, USB host (2)	USB 2.0, 10/100/1000 BaseTX, USB host (2)	USB 2.0, 10/100/1000BaseTX, USB host (2)	USB 2.0, 10/100/1000 BaseTX, USB host (2)
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.14
	EMULATIONS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS
<b>NETWORK</b>	INTERFACES	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	NETWORK PROTOCOLS	TCP/IP, Net BEUI	TC P/IP, Net BEUI	TCP/IP, Net BEUI	TC P/IP, Net BEUI
	OPERATING SYSTEMS	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022
<b>SCAN</b>	SCAN TYPE	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w
	SCAN RESOLUTION	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	INTERFACES	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0
	NETWORK PROTOCOLS	TCP/IP	TCP/IP	TCP/IP	TCP/IP
<b>FAX</b>	ORIGINALS	--	max A4	--	max A4
	MODEM SPEED	--	33.6 kbps	--	33.6 kbps
	COMPRESSION METHOD	--	JBIG, MMR, MR, MH	--	JBIG, MMR, MR, MH
	ONE-TOUCH DIAL/ABBR. DIAL	--	100/200	--	100/200

# A4 Print Systems



## P-C2650DW

<b>PRINT FORMAT</b>	A6R-A4
<b>PRINT SPEED</b>	26 A4 pages/min in colour and b/w
<b>PRINT RESOLUTION</b>	600 x 600 dpi, 9,600 x 600 dpi level, 1,200 x 1,200 dpi (reduced speed)
<b>STANDARD PAPER FEED</b>	300 (1 x 250 + 50 sheets)
<b>OPTIONAL PAPER FEED</b>	1 x 250 sheets
<b>DUPLEX</b>	Standard
<b>PROCESSOR</b>	Cortex-A9 / 800 MHz
<b>PRINT MEMORY</b>	512 MB (max 512 MB)
<b>INTERFACES</b>	USB 2.0, 10/100/1000BaseTX, USB host, SD slot, Wi-Fi
<b>NETWORK CARD OPTIONAL</b>	--
<b>EMULATIONS</b>	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS, Open XPS



## P-C3563DN

<b>PRINT FORMAT</b>	A6R-A4
<b>PRINT SPEED</b>	35 A4 pages/min in colour and b/w
<b>PRINT RESOLUTION</b>	600 x 600 dpi, max 1,200 x 1,200 dpi (reduced speed)
<b>STANDARD PAPER FEED</b>	650 (1 x 550 + 100 sheets)
<b>OPTIONAL PAPER FEED</b>	3 x 550 sheets
<b>DUPLEX</b>	Standard
<b>PROCESSOR</b>	ARM Cortex-A9 dual core / 1.2 GHz
<b>PRINT MEMORY</b>	1 GB RAM (max 1 GB RAM)
<b>INTERFACES</b>	USB 2.0, 10/100/1000BaseTX, USB host (2)
<b>NETWORK CARD OPTIONAL</b>	IB-50 Gigabit Ethernet, IB-37 / IB-51 WLAN card
<b>EMULATIONS</b>	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS



## P-C4063DN

<b>PRINT FORMAT</b>	A6R-A4
<b>PRINT SPEED</b>	40 A4 pages/min in colour and b/w
<b>PRINT RESOLUTION</b>	600 x 600 dpi, max 1,200 x 1,200 dpi (reduced speed)
<b>STANDARD PAPER FEED</b>	650 (1 x 550 + 100 sheets)
<b>OPTIONAL PAPER FEED</b>	3 x 550 sheets
<b>DUPLEX</b>	Standard
<b>PROCESSOR</b>	ARM Cortex-A9 dual core / 1.2 GHz
<b>PRINT MEMORY</b>	1 GB RAM (max 3 GB RAM)
<b>INTERFACES</b>	USB 2.0, 10/100/1000BaseTX, USB host (2)
<b>NETWORK CARD OPTIONAL</b>	IB-50 Gigabit Ethernet, IB-37 / IB-51 WLAN card
<b>EMULATIONS</b>	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS



## P458ci

<b>PRINT FORMAT</b>	A6R-A4
<b>PRINT SPEED</b>	45 A4 pages/min in colour and b/w
<b>PRINT RESOLUTION</b>	600 x 600 dpi, max 1,200 x 1,200 dpi (reduced speed)
<b>STANDARD PAPER FEED</b>	650 (1 x 550 + 100 sheets)
<b>OPTIONAL PAPER FEED</b>	4 x 550 sheets
<b>DUPLEX</b>	Standard
<b>PROCESSOR</b>	ARM Cortex-A9 dual core / 1.2 GHz
<b>PRINT MEMORY</b>	1 GB RAM (max 3 GB RAM)
<b>INTERFACES</b>	USB 2.0, 10/100/1000BaseTX, USB host (2)
<b>NETWORK CARD OPTIONAL</b>	IB-50 Gigabit Ethernet, IB-37 / IB-51 WLAN card
<b>EMULATIONS</b>	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS



# A3 Multifunctional Systems



Optional features are marked in grey font.

		P-2540i MFP	3263i	4063i
<b>COPY</b>	COPY SPEED	25 A4 / 12 A3 pages/min	32 A4 / 17 A3 pages/min	40 A4 / 21 A3 pages/min
	COPY RESOLUTION	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	GREYSCALES	256	256	256
	STANDARD PAPER FEED	600 (1 x 500 + 100 sheets)	1,100 (2 x 500 + 100 sheets)	1,100 (2 x 500 + 100 sheets)
	OPTIONAL PAPER FEED	1 or 2 x 500 sheets	2 x 500 sheets or 2 x 1,500	2 x 500 sheets or 2 x 1,500
	PAPER CAPACITY, MAX	1,600 sheets	4,100 sheets	4,100 sheets
	PAPER FORMAT	A6R-A3	A6R-A3	A6R-A3
	ORIGINAL FEEDER	Standard	Option: DP-7140, DP-7150, DP-7160 or DP-7170	Option: DP-7140, DP-7150, DP-7160 or DP-7170
	DUPLEX	Standard	Standard	Standard
	SYSTEM MEMORY	1 GB (max 3 GB)	4 GB RAM, 32 GB SSD/320 GB HDD or 1 TB HDD	4 GB RAM, 32 GB SSD/320 GB HDD or 1 TB HDD
ZOOM	25%–400%	25%–400%	25%–400%	
CABINET	Option: no. 20	Option: no. 70	Option: no. 70	
<b>PRINT</b>	TYPE	Integrated within the system	Integrated within the system	Integrated within the system
	INTERFACES	USB 2.0, 10/100/1000BaseTX, USB host (2)	USB 3.0, USB 2.0, 10/100/1000BaseTX, USB host, NFC	USB 3.0, USB 2.0, 10/100/1000BaseTX, USB host, NFC
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.9	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.9	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.9
	EMULATIONS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIe, PDF 1.7	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIe	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIe
<b>NETWORK</b>	INTERFACES	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	NETWORK PROTOCOLS	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	OPERATING SYSTEMS	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022
<b>SCAN</b>	SCAN TYPE	CIS colour and b/w	CCD colour and b/w	CCD colour and b/w
	SCAN RESOLUTION	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	INTERFACES	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX	10/100/1000BaseTX
	NETWORK PROTOCOLS	TCP/IP	TCP/IP	TCP/IP
<b>FAX</b>	ORIGINALS	max A3	max A3	max A3
	MODEM SPEED	33.6 kbps	33.6 kbps	33.6 kbps
	COMPRESSION METHOD	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	ONE-TOUCH DIAL/ABBR. DIAL	100/200	1,000/2,000	1,000/2,000

# A3 Multifunctional Systems



Optional features are marked in grey font.

		5058i	6058i	7058i	8057i
<b>COPY</b>	COPY SPEED	50 A4 / 25 A3 pages/min	60 A4 / 30 A3 pages/min	70 A4 / 35 A3 pages/min	80 A4 / 40 A3 pages/min
	COPY RESOLUTION	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	GREYSCALES	256	256	256	256
	STANDARD PAPER FEED	1,150 (2 x 500 + 150 sheets)	1,150 (2 x 500 + 150 sheets)	1,150 (2 x 500 + 150 sheets)	4,150 (2 x 500 + 2 x 1,500 + 150 sheets)
	OPTIONAL PAPER FEED	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible
	PAPER CAPACITY, MAX	7,150 sheets	7,650 sheets	7,650 sheets	7,650 sheets
	PAPER FORMAT	A6R-SRA3/A3+	A6R-SRA3/A3+	A6R-SRA3/A3+	A6R-A3+
	ORIGINAL FEEDER	Option: DP-7150, DP-7160 or DP-7170	Option: DP-7150, DP-7160 or DP-7170	Option: DP-7150, DP-7160 or DP-7170	Standard (dual scan with multi-feed detection)
	DUPLEX	Standard	Standard	Standard	Standard
	SYSTEM MEMORY	4 GB RAM, 64 GB SSD/320 GB HDD or 1 TB HDD	4 GB RAM, 64 GB SSD/320 GB HDD or 1 TB HDD	4 GB RAM, 64 GB SSD/320 GB HDD or 1 TB HDD	4.5 GB RAM, 8 GB SSD/320 GB HDD
ZOOM	25%-400%	25%-400%	25%-400%	25%-400%	
CABINET	Option: no. 81	Option: no. 81	Option: no. 81	--	
<b>PRINT</b>	TYPE	Integrated within the system	Integrated within the system	Integrated within the system	Integrated within the system
	INTERFACES	USB 3.0, USB 2.0, 10/100/1000BaseTX, USB host, NFC	USB 3.0, USB 2.0, 10/100/1000BaseTX, USB host, NFC	USB 3.0, USB 2.0, 10/100/1000BaseTX, USB host, NFC	USB 2.0, 10/100/1000BaseTX, USB host, NFC
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.9	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.9	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.9	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.9
	EMULATIONS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, PDF 2.0, XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, PDF 2.0, XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, PDF 2.0, XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIe
<b>NETWORK</b>	INTERFACES	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	NETWORK PROTOCOLS	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	OPERATING SYSTEMS	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022
<b>SCAN</b>	SCAN TYPE	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w
	SCAN RESOLUTION	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	INTERFACES	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	NETWORK PROTOCOLS	TCP/IP	TCP/IP	TCP/IP	TCP/IP
<b>FAX</b>	ORIGINALS	max A3	max A3	max A3	max A3
	MODEM SPEED	33.6 kbps	33.6 kbps	33.6 kbps	33.6 kbps
	COMPRESSION METHOD	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	ONE-TOUCH DIAL/ABBR. DIAL	1,000/2,000	1,000/2,000	1,000/2,000	1,000/2,000

# A4 Multifunctional Systems



## P-3521 MFP

## P-3527w MFP

<b>COPY</b>	COPY SPEED	35 A4 pages/min	35 A4 pages/min
	COPY RESOLUTION	600 x 600 dpi	600 x 600 dpi
	GREYSCALES	256	256
	STANDARD PAPER FEED	350 (1 x 250 + 100 sheets)	350 (1 x 250 + 100 sheets)
	OPTIONAL PAPER FEED	2 x 250 sheets	2 x 250 sheets
	PAPER CAPACITY, MAX	850 sheets	850 sheets
	PAPER FORMAT	A6R-A4	A6R-A4
	ORIGINAL FEEDER	Standard	Standard
	DUPLEX	Standard	Standard
	SYSTEM MEMORY	512 MB RAM (max 1,536 MB RAM)	512 MB RAM (max 1,536 MB RAM)
ZOOM	25%–400%	25%–400%	
CABINET	Option: no. 78	Option: no. 78	
<b>PRINT</b>	TYPE	Integrated within the system	Integrated within the system
	INTERFACES	10/100/1000BaseTX, USB 2.0, USB host, SD slot	10/100/1000BaseTX, USB 2.0, USB host, SD slot, Wi-Fi
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Mac ex OS 10.9	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Mac ex OS 10.9
	EMULATIONS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter X24E, Epson LQ-850, PDF 1.7, XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter X24E, Epson LQ-850, PDF 1.7, XPS
<b>NETWORK</b>	INTERFACES	10/100/1000BaseTX	10/100/1000BaseTX
	NETWORK PROTOCOLS	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	OPERATING SYSTEMS	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022
<b>SCAN</b>	SCAN TYPE	CCD colour and b/w	CCD colour and b/w
	SCAN RESOLUTION	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	INTERFACES	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0
	NETWORK PROTOCOLS	TCP/IP	TCP/IP
<b>FAX</b>	ORIGINALS	--	max A4
	MODEM SPEED	--	33.6 kbps
	COMPRESSION METHOD	--	JBIG, MMR, MR, MH
	ONE-TOUCH DIAL/ABBR. DIAL	--	100/200

# A4 Multifunctional Systems



		P-4020 MFP	P-4025w MFP	P-4026iw MFP
<b>COPY</b>	COPY SPEED	40 A4 pages/min	40 A4 pages/min	40 A4 pages/min
	COPY RESOLUTION	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	GREYSCALES	256	256	256
	STANDARD PAPER FEED	350 (1 x 250 + 100 sheets)	350 (1 x 250 + 100 sheets)	350 (1 x 250 + 100 sheets)
	OPTIONAL PAPER FEED	2 x 250 sheets	2 x 250 sheets	2 x 250 sheets
	PAPER CAPACITY, MAX	850 sheets	850 sheets	850 sheets
	PAPER FORMAT	A6R-A4	A6R-A4	A6R-A4
	ORIGINAL FEEDER	Standard (Duplex-Scan)	Standard (Duplex-Scan)	Standard (Duplex-Scan)
	DUPLEX	Standard	Standard	Standard
	SYSTEM MEMORY	512 MB RAM (max 1,536 MB RAM)	512 MB RAM (max 1,536 MB RAM)	512 MB RAM (max 1,536 MB RAM)
ZOOM	25%–400%	25%–400%	25%–400%	
CABINET	Option: no. 78	Option: no. 78	Option: no. 78	
<b>PRINT</b>	TYPE	Integrated within the system	Integrated within the system	Integrated within the system
	INTERFACES	10/100/1000BaseTX, USB 2.0, USB host, SD slot	10/100/1000BaseTX, USB 2.0, USB host, SD slot, Wi-Fi	10/100/1000BaseTX, USB 2.0, USB host, SD slot, Wi-Fi
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.9	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Mac ex OS 10.9	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.9
EMULATIONS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS	
<b>NETWORK</b>	INTERFACES	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	NETWORK PROTOCOLS	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	OPERATING SYSTEMS	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022	Windows 8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022
<b>SCAN</b>	SCAN TYPE	CIS colour and b/w	CIS colour and b/w	CIS colour and b/w
	SCAN RESOLUTION	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	INTERFACES	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0
	NETWORK PROTOCOLS	TCP/IP	TCP/IP	TCP/IP
<b>FAX</b>	ORIGINALS	--	max A4	max A4
	MODEM SPEED	--	33.6 kbps	33.6 kbps
	COMPRESSION METHOD	--	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	ONE-TOUCH DIAL/ABBR. DIAL	--	100/200	100/200

# A4 Multifunctional Systems

Optional features are marked in grey font.



		P-4532i MFP	P-4539i MFP	P-4532i MFP	P-4539i MFP
<b>COPIER</b>	COPY SPEED	45 A4 pages/min	45 A4 pages/min	45 A4 pages/min	45 A4 pages/min
	COPY RESOLUTION	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	GREYSCALES	256	256	256	256
	STANDARD PAPER FEED	600 (1 x 500 + 100 sheets)	600 (1 x 500 + 100 sheets)	600 (1 x 500 + 100 sheets)	600 (1 x 500 + 100 sheets)
	OPTIONAL PAPER FEED	4 x 500 sheets	4 x 500 sheets	4 x 500 sheets	4 x 500 sheets
	PAPER CAPACITY, MAX	2,600 sheets	2,600 sheets	2,600 sheets	2,600 sheets
	PAPER FORMAT	A6R-A4	A6R-A4	A6R-A4	A6R-A4
	ORIGINAL FEEDER	Standard	Standard	Standard	Standard
	DUPLEX	Standard	Standard	Standard	Standard
	SYSTEM MEMORY	1 GB RAM (max 3 GB RAM), 64/256/512 GB SSD	1 GB RAM (max 3 GB RAM), 64/256/512 GB SSD	1.5 GB RAM (max 3.5 GB RAM), 64/256/512 GB SSD	1.5 GB RAM (max 3.5 GB RAM), 64/256/512 GB SSD
ZOOM	25%–400%	25%–400%	25%–400%	25%–400%	
CABINET	Option: high no. 79, low no. 80	Option: high no. 79, low no. 80	Option: high no. 79, low no. 80	Option: high no. 79, low no. 80	
<b>PRINT</b>	TYPE	Integrated within the system	Integrated within the system	Integrated within the system	Integrated within the system
	INTERFACES	USB 2.0, 10/100/1000BaseTX, USB host	USB 2.0, 10/100/1000BaseTX, USB host	USB 2.0, 10/100/1000BaseTX, USB host	USB 2.0, 10/100/1000BaseTX, USB host
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.14
EMULATIONS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS	
<b>NETWORK</b>	INTERFACES	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	NETWORK PROTOCOLS	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022
<b>SCAN</b>	SCAN TYPE	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w
	SCAN RESOLUTION	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	INTERFACES	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0
	NETWORK PROTOCOLS	TCP/IP	TCP/IP	TCP/IP	TCP/IP
<b>FAX</b>	ORIGINALS	--	max A4	--	max A4
	MODEM SPEED	--	33.6 kbps	--	33.6 kbps
	COMPRESSION METHOD	--	JBIG, MMR, MR, MH	--	JBIG, MMR, MR, MH
	ONE-TOUCH DIAL/ABBR. DIAL	--	22/100	--	100/200

# A4 Multifunctional Systems

Optional features are marked in grey font.



		P-5539i MFP	P-6038i MFP
<b>COPY</b>	COPY SPEED	55 A4 pages/min	60 A4 pages/min
	COPY RESOLUTION	600 x 600 dpi	600 x 600 dpi
	GREYSCALES	256	256
	STANDARD PAPER FEED	600 (1 x 500 + 100 sheets)	600 (1 x 500 + 100 sheets)
	OPTIONAL PAPER FEED	4 x 500 sheets	4 x 500 sheets
	PAPER CAPACITY, MAX	2,600 sheets	2,600 sheets
	PAPER FORMAT	A6R-A4	A6R-A4
	ORIGINAL FEEDER	Standard (Duplex-Scan)	Standard (dual scan with multi-feed detection)
	DUPLEX	Standard	Standard
	SYSTEM MEMORY	1.5 GB RAM (max 3.5 GB RAM), 64/256/512 GB SSD	1.5 GB RAM (max 3.5 GB RAM), 64/256/512 GB SSD
ZOOM	25%–400%	25%–400%	
CABINET	Option: high no. 79, low no. 80	Option: high no. 79, low no. 80	
<b>PRINT</b>	TYPE	Integrated within the system	Integrated within the system
	INTERFACES	USB 2.0, 10/100/1000BaseTX, USB host	USB 2.0, 10/100/1000BaseTX, USB host, SD slot
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.14	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac ex OS 10.14
EMULATIONS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS	
<b>NETWORK</b>	INTERFACES	10/100/1000BaseTX	10/100/1000BaseTX
	NETWORK PROTOCOLS	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	OPERATING SYSTEMS	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022	Windows 8/8.1/10/11, Server 2012/2012 R2/2016/2019/2022
<b>SCAN</b>	SCAN TYPE	CCD colour and b/w	CCD colour and b/w
	SCAN RESOLUTION	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	INTERFACES	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0
	NETWORK PROTOCOLS	TCP/IP	TCP/IP
<b>FAX</b>	ORIGINALS	max A4	max A4
	MODEM SPEED	33.6 kbps	33.6 kbps
	COMPRESSION METHOD	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	ONE-TOUCH DIAL/ABBR. DIAL	100/200	100/200

# A3 Print Systems



## P-6040DN

<b>PRINT FORMAT</b>	A6R-SRA3
<b>PRINT SPEED</b>	60 A4 / 30 A3 pages/min
<b>PRINT RESOLUTION</b>	1,200 x 1,200 dpi
<b>STANDARD PAPER FEED</b>	1,150 (2 x 500 + 150 sheets)
<b>OPTIONAL PAPER FEED</b>	2 x 500, 2 x 1,500, 3,000 sheets
<b>DUPLEX</b>	Standard
<b>PROCESSOR</b>	Freescale QoriQ T1024 (Dual Core) 1.2 GHz
<b>PRINT MEMORY</b>	4 GB RAM, 8 GB SSD, 320 GB HDD
<b>INTERFACES</b>	USB 2.0, USB host, 10/100/1000BaseTX, NFC
<b>OPTIONAL INTERFACES</b>	--
<b>EMULATIONS</b>	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), XPS, PDF 1.7, PRESCRIBE IIe

# A4 Print Systems



## P-3522DW

<b>PRINT FORMAT</b>	A6R-A4
<b>PRINT SPEED</b>	35 A4 pages/min
<b>PRINT RESOLUTION</b>	600 x 600 dpi, 1,200 x 1,200 dpi
<b>STANDARD PAPER FEED</b>	350 (250 + 100 sheets)
<b>OPTIONAL PAPER FEED</b>	2 x 250 sheets
<b>DUPLEX</b>	Standard
<b>PROCESSOR</b>	Cortex-A9 / 800 MHz
<b>PRINT MEMORY</b>	256 MB (max 256 MB)
<b>INTERFACES</b>	10/100/1000BaseTX, USB 2.0, USB host, SD slot, Wi-Fi
<b>OPTIONAL INTERFACES</b>	--
<b>EMULATIONS</b>	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS



## P-4020DN

<b>PRINT FORMAT</b>	A6R-A4
<b>PRINT SPEED</b>	40 A4 pages/min
<b>PRINT RESOLUTION</b>	600 x 600 dpi, 1,200 x 1,200 dpi
<b>STANDARD PAPER FEED</b>	350 (250 + 100 sheets)
<b>OPTIONAL PAPER FEED</b>	2 x 250 sheets
<b>DUPLEX</b>	Standard
<b>PROCESSOR</b>	Cortex-A9 / 800 MHz
<b>PRINT MEMORY</b>	256 MB (max 256 MB)
<b>INTERFACES</b>	10/100/1000BaseTX, USB 2.0, USB host, SD slot
<b>OPTIONAL INTERFACES</b>	--
<b>EMULATIONS</b>	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS

## P-4020DW

<b>PRINT FORMAT</b>	A6R-A4
<b>PRINT SPEED</b>	40 A4 pages/min
<b>PRINT RESOLUTION</b>	600 x 600 dpi, 1,200 x 1,200 dpi
<b>STANDARD PAPER FEED</b>	350 (250 + 100 sheets)
<b>OPTIONAL PAPER FEED</b>	2 x 250 sheets
<b>DUPLEX</b>	Standard
<b>PROCESSOR</b>	Cortex-A9 / 800 MHz
<b>PRINT MEMORY</b>	256 MB (max 256 MB)
<b>INTERFACES</b>	10/100/1000BaseTX, USB 2.0, USB host, SD slot, Wi-Fi
<b>OPTIONAL INTERFACES</b>	--
<b>EMULATIONS</b>	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS



## P-4534DN

<b>PRINT FORMAT</b>	A6R-A4
<b>PRINT SPEED</b>	45 A4 pages/min
<b>PRINT RESOLUTION</b>	1,200 x 1,200 dpi
<b>STANDARD PAPER FEED</b>	600 (500 + 100 sheets)
<b>OPTIONAL PAPER FEED</b>	4 x 500 sheets
<b>DUPLEX</b>	Standard
<b>PROCESSOR</b>	ARM Cortex-A53 Dual Core, 1,4 GHz
<b>PRINT MEMORY</b>	512 MB (max 2.5 GB)
<b>INTERFACES</b>	10/100/1000BaseTX, USB 2.0, USB host (2), SD slot
<b>OPTIONAL INTERFACES</b>	IEEE 1284 parallel, 10/100/1000BaseTX, WLAN card
<b>EMULATIONS</b>	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS



## P-5034DN

<b>PRINT FORMAT</b>	A6R-A4
<b>PRINT SPEED</b>	50 A4 pages/min
<b>PRINT RESOLUTION</b>	1,200 x 1,200 dpi
<b>STANDARD PAPER FEED</b>	600 (500 + 100 sheets)
<b>OPTIONAL PAPER FEED</b>	4 x 500 sheets
<b>DUPLEX</b>	Standard
<b>PROCESSOR</b>	ARM Cortex-A53 Dual Core, 1,4 GHz
<b>PRINT MEMORY</b>	512 MB (max 2.5 GB)
<b>INTERFACES</b>	10/100/1000BaseTX, USB 2.0, USB host (2), SD slot
<b>OPTIONAL INTERFACES</b>	IEEE 1284 parallel, 10/100/1000BaseTX, WLAN card
<b>EMULATIONS</b>	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS

## P-5534DN

<b>PRINT FORMAT</b>	A6R-A4
<b>PRINT SPEED</b>	55 A4 pages/min
<b>PRINT RESOLUTION</b>	1,200 x 1,200 dpi
<b>STANDARD PAPER FEED</b>	600 (500 + 100 sheets)
<b>OPTIONAL PAPER FEED</b>	4 x 500 sheets
<b>DUPLEX</b>	Standard
<b>PROCESSOR</b>	ARM Cortex-A53 Dual Core, 1,4 GHz
<b>PRINT MEMORY</b>	512 MB (max 2.5 GB)
<b>INTERFACES</b>	10/100/1000BaseTX, USB 2.0, USB host (2), SD slot
<b>OPTIONAL INTERFACES</b>	IEEE 1284 parallel, 10/100/1000BaseTX, WLAN card
<b>EMULATIONS</b>	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS

## P-6034DN

<b>PRINT FORMAT</b>	A6R-A4
<b>PRINT SPEED</b>	60 A4 pages/min
<b>PRINT RESOLUTION</b>	1,200 x 1,200 dpi
<b>STANDARD PAPER FEED</b>	600 (500 + 100 sheets)
<b>OPTIONAL PAPER FEED</b>	4 x 500 sheets
<b>DUPLEX</b>	Standard
<b>PROCESSOR</b>	ARM Cortex-A53 Dual Core, 1,4 GHz
<b>PRINT MEMORY</b>	512 MB (max 2.5 GB)
<b>INTERFACES</b>	10/100/1000BaseTX, USB 2.0, USB host (2), SD slot
<b>OPTIONAL INTERFACES</b>	IEEE 1284 parallel, 10/100/1000BaseTX, WLAN card
<b>EMULATIONS</b>	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS



**UTAX recommends** the use of original UTAX accessories for trouble-free operation of your system. For recommended print media refer to the user manual. UTAX and the UTAX logo are registered trademarks of TA Triumph-Adler GmbH. All other brand names referred to are registered trademarks of the respective manufacturers.



Your UTAX dealer

**About UTAX**

UTAX is a registered trademark of the TA Triumph-Adler GmbH. The Hamburg-based company specializes in the sale of high-quality printing and copying systems. The broad product portfolio includes hardware as well as software applications. In addition to copying, printing and multifunctional systems (MFP) for the office workplace, UTAX supplies customized IT solutions and services as well as comprehensive consulting for efficient document processes in companies. In Germany, the UTAX brand is distributed through a network of over 200 authorized dealers. Internationally, the company operates in over 40 countries in the EMEA region.

