

Outstanding performance even under major pressure.

Is maximum productivity combined with consistent quality and utmost flexibility your top goal? Then our 7057i and 8057i A3 b/w multifunctional systems are virtually made for you. The systems offer optimised performance, which is evident from the rapid output of the first page. At the same time, integrated OCR text recognition guarantees significantly improved efficiency. Scans can be transformed into new, editable and searchable files that can be stored in a pre-defined folder at just the touch of a button. And the best thing about that: only the scanned documents are searchable, but your confidential data on the system is not!



DIGITAL • • • • MULTIFUNCTIONAL SYSTEM 7057i / 8057i

Copy / Print / Scan / Fax

A3

HIGHLIGHTS:

Sheer reliability: in order to make office workflows more efficient, the new systems feature a dual scanner as standard, which includes an ultrasonic sensor that prevents multiple originals from being fed in at the same time during scanning. Up to 270 originals can be scanned and digitised in one run at a rate of up to 220 images per minute in colour and b/w at 300 dpi.

Production line levels of efficiency: these systems offer the ideal set-up for carrying out large print jobs. The optimised output speed of the first copied or printed page is merely the beginning of the value-added chain. The systems can process a paper weights up to 300 g/m² from a maximum of eight different paper feeds in one printing process, maintaining a total paper capacity of 7,650 sheets. All this combined with the 4,000 sheet finisher*– not to mention the brochure modules* – gives rise to a professional, folded end product.

Integrated security: you can count on these systems when it comes to keeping your confidential data secure. Data to be copied, scanned and printed is protected by means of hard drive encryption. The Trusted Platform Module (TPM) offers additional support to this end. This security chip is integrated within the system. It saves and manages encryption codes generated on the device in the TPM's memory. Accessing the memory via external devices is – of course – impossible.

Operation is a breeze: the large 10.1 inch touch-sensitive colour display doesn't just look stylish – it will win you over with its intuitive operation and clear menu navigation. Additionally, the integrated HyPASTM interface enables you to use a range of different HyPASTM applications, as well as to incorporate customer-specific software solutions that will make your working day more sustainable and efficient now and in the long term.

7057i / 8057i

TECHNICAL DATA

GENERAL

Туре Console Unit

Function Copy, print, scan, optional: fax

Print technology Laser b/w

Original format max A3 from platen glass

Original feeder Dual scanner with ultrasonic sensor for multi-feed detection (AGR-A3, capacity

270 sheet A4, paper weight 35-220 g/m² [DIN A5R-DIN A3])

Copy/print speed

max 70 A4 pages/min and max 35 A3 pages/min,

max 80 A4 pages/min and max 40 A3 pages/min

7057i: 4.2/4.8 seconds*, 1st page (Copy/Print)

8057i: 3.7/4.1 seconds

Warm-up time 30 seconds Copy resolution 600×600 dpi

Greyscales 256

Paper feed 2 x 500 sheet universal cassettes (A5R-A3+ (max 305 x 457 mm)), 2 x 1,500

sheet large capacity cassette (A4), 150 sheet multi-bypass (A6R-A3+, Banner (305 x 1,219 mm)), A3+ only for printing

Universal cassette 60-256 g/m², multi-bypass 60-300 g/m², duplex 60-256 Paper weights

250 sheet A4 (upper tray). 100 sheet (lower tray) with Copy tray type D*** Paper output

4.5 GB RAM, 8 GB SSD/320 GB HDD** System memory

1-9.999 copies Continuous copying

25 %-400 % in steps of 1 %

Functions Adjustable capacitive colour touch

screen (10.1 inch), duplex, 1,000 management codes, skip blank pages, Trusted Platform Module (TPM), secure boot and run time integrity

check etc

DIMENSIONS/WEIGHT

1,234 x 750 x 822 mm (H x W x D) Dimensions

Weight approx. 150 kg

ENVIRONMENT

220/240 V, 50/60 Hz Mains voltage

approx. 2,400 W max, approx. 1,110/1,170 W in operation (7057i/8057i), approx. 110 W in stand-by mode, approx. 0.7 W in sleep Power consumption

GS/TÜV. CE Safety

PRINT SYSTEM

Integrated within the system Type

Print format A6R-A3+

max 1,200 x 1,200 dpi Print resolution

Freescale OorlO T1042 (Dual Core) 1.4 GHz Processor Interfaces USB 2.0, 10/100/1000BaseTX, USB host,

Network protocols TCP/IP Net REUI

Windows 7/8.1/10. Server 2008/2008 Operating systems

R2/2012/2012 R2/2016/2019, Novell NetWare***, Linux, Mac ex OS 10.9

PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), XPS, PDF, PRESCRIBE IIe **Emulations**

Functions

USB direct printing, PDF/XPS direct printing, IPsec, SNMPv3, printing of e-mails, private printing, barcode printing, Mobile Print (Android/iOS)/Apple AirPrint, Google

SCAN SYSTEM

Scan type CCD colour and b/w

Scan format max A3

max 120/220 (simplex/duplex) A4 Scan speed originals/min in colour and b/w (300 dpi)

200 dpi, 300 dpi, 400 dpi, 600 dpi Scan resolution Scan mode Photo, text, photo/text, OCR

TIFF, PDF, PDF/A, high compression PDF, encrypted PDF, JPEG, XPS, Open XPS File types

Interfaces 10/100/1000BaseTX

Network protocol TCP/IP

Windows 7/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019 Operating systems

Functions Scan to SMB, scan to e-mail, scan to FTP

scan to USB, TWAIN scan, WIA scan, SMTP

authentication, LDAP

OPTIONAL FAX SYSTEM 12

Compatibility Super G3 **Original format** max A3 33.6 kbps Modem speed

3 seconds or less using JBIG Transmission speed Compression method JBIG, MMR, MR, MH

OPTIONAL FAX SYSTEM 12

Standard (200 \times 100 dpi), fine (200 \times 200 dpi), super fine (200 \times 400 dpi), ultra fine (400 \times 400 dpi), 600 \times 600 dpi Fax resolution

IF IT WORX, IT'S

UITA

Abbreviated dial 2,000 numbers 1,000 numbers One touch dial 500 numbers

Windows 7/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016/2019 Operating systems

Network fax driver, automatic redialling, Functions

delayed transmission, max 2 fax kits for parallel transmission and reception

OPTIONS

Finisher

DF-7110 (capacity: 4,000 sheet A4, stapling max 65 sheet A4), DF-7130 (capacity: 4,000 sheet A4, stapling max 100 sheet 4,JUU sheet A4, stapling max 100 sheet A4), PH-7C hole punch unit for DF-7110 and DF-7130, BF-730 brochure module for DF-7110 (max 20 sheet saddle stitching and folding A4/A3, th-folding max 5 sheet A4), BF-9100 brochure module for DF-7130 (max 20 sheet saddle stitching and folding A4/A3, th-folding max 5 sheet A4), MT-730 (B) Multi tray for DF-7110

Paper feed

PF-730 (B) (2 \times 500 sheet universal cassettes (A5R-A3+)), PF-740 (B) (2 \times 1,500 sheet large capacity cassette (A4)), PF-7130 (500 sheet multi-purpose cassette (A5R-A3+), required if PF-730 (B)/PF-740 (B) is installed), PF-7120 (3,000 sheet large capacity tray (A4), side deck)

Other options

Internet fax kit (A), Card authentication kit (B), Keyboard holder 10, Banner guide (A), UG-33 ThinPrint® kit, UG-34 Emulation option kit, IB-50 Gigabit Ethernet card, IB-51 WLAN card, IB-55 WLAN card, IR-7120 Numeric Keyboard (10 keys), Copy tray

type D

* Depending on operating status

** For copy, print, scan, fax

*** optional

Specifications subject to change without notice. Image shows machine with optional accessories.

UTAX has been a trade mark for professional office technology since 1961. As the partner of a German wide network and international distribution, we are specialised in the distribution and integration of printing, copying and multifunctional systems in corporate IT and public sector, amongst others. With the MDS solution UTAX smart for example, output systems can be controlled regardless of the manufacturer and the infrastructure can be optimised in line with demands. UTAX recommends the use of original UTAX accessories for trouble-free operation of your system. For recommended print media refer to the user manual. UTAX and the UTAX logo are registered trade marks of TA Triumph-Adler GmbH. All other brand names referred to are registered trade marks of the respective manufacturers.













Your UTAX-dealer